

ALCATEL-LUCENT 8002 AND 8012 DESKPHONES

The Alcatel-Lucent 8002 and 8012 DeskPhones are cost-effective, entry-level phones that offer SIP telephony for essential communications in a business-grade design. They are the perfect voice companion to desktop-centric activities to ensure always-on connectivity and fast access to the enterprise directory. Their energy efficiency combined with a LAN connector for connection to your PC and integration with Alcatel-Lucent communication and management platforms help reduce OPEX and total cost of ownership (TCO).



FEATURES

- Standard SIP telephony based on compliance to RFC standards
- Business-grade design
- Third-party call control
- Integration with Alcatel-Lucent communication platforms
- Centralized management
- Hands-free option
- Energy efficiency
- Unified directory access

BENEFITS

- Meet eco-friendly and low energy consumption standards
- Offer always-on connectivity to ensure continuity of critical communications
- Integrate completely in a multi-device environment
- Can be the ideal companion to a softphone for better audio comfort
- Simplify operations and reduce OPEX and TCO through a seamless and single management platform shared with other devices, applications and networking elements



TECHNICAL SPECIFICATIONS

Phone only

- Height: 190 mm (7.48 in.)
- Width: 161 mm (6.33 in.)
- Depth: 196 mm (7.71 in.)
- Weight: 810 g (1.78 lb) including handset
- Color: Black
- Adjustable foot stand: 0° or 50°
- Ingress protection (IP): 20
- Redial/Mute
- Local interphony

Display

- One-line, black and white
- 20 alphanumeric characters

Audio characteristics

- Hands-free capability
- Comfort handset
- Volume controls
- Mute control
- Support for G.711 A law/ μ law and G.729 CODECS
- Answer from audio equipment

Keys and navigation (physical keys with LED)

Audio

- Volume control keys (+ and -)
- Hands-free, loudspeaker and external audio management key
- Mute key

Application keys

- Message Waiting Indication
- Missed Call Waiting Indication

Navigation

- Home key for immediate access to home menu and dial by name
- 'C'ancel key
- OK and up/down keys to access menu
 - Admin settings
 - Device settings
 - Call log
 - Dialing menu
 - Routing
 - Local directory

Accessories

- 5-V power adapter (ref. 3MG27026xx)
- Headset (see catalog for latest list)

Power

- 802.3 AZ (Energy-Efficient Ethernet) support
- 802.3AF Power over Ethernet (PoE) (Class 1) support (8002 DeskPhone)
- 802.3AF Power over Ethernet (PoE) (Class 2) support (8012 DeskPhone)
- Maximum power for the 8002 in use \leq 2.68 W
- Maximum power for the 8012 in use \leq 4.15 W (on call and PC connected)

Connectivity

- LAN: 10/100/1000 Ethernet (8012)
- LAN: 10/100 Ethernet (8002)
- PC through integrated 10/100/1000 Ethernet switch (8012 DeskPhone)
- 3.5-mm jack headset port (8012 DeskPhone)
- RJ-9 connector for handset
- Mini-USB connector for power adapter

Centralized management

- DHCP/AVA
- LLDP-MED extensions for VLAN assignment and PoE management
- HTTP/HTTPS
- SNMP synchronization

Quality of service*

- 802.1 P/Q, DSCP
- RTCP-XR QoS and tickets support: In-call and end-of-call

Security*

- HTTPS for secured HTTP access
- 802.1x Message Digest 5 (MD5)/TLS: For authentication and management of customer certificates (with centralized deployment)
- Denial of Service (DoS) attack protection: Flooding
- ARP spoofing protection

Internationalization and localization

- Support for 22 languages

Accessibility

- Hearing Aid Compatibility (HAC)
- Blinking LED for incoming calls (back and front visibility)

Telephony

- SIP support for telephony services
- Make/Receive call
- Call transfer
- Call Hold/Resume
- 3-way conference
- Multi-line management
- 3rd party call control (3PCC)
- Call log for:
 - Missed calls
 - Outgoing calls
 - Incoming calls
- Dual-tone multi-frequency (DTMF)
- Dial by name**
- CLIR/CLID
- Local auto answer (interphony)

Contact management

- Local directory: add, edit and delete local contacts
- Unified directory access**

Advanced communication services*

- Routing management (local or centralized forward depending on the system)

System interoperability

- Alcatel-Lucent OpenTouch™ products, including Alcatel-Lucent OmniVista™ 8770 Network Management System, Release 1.2 and later
- Alcatel-Lucent OmniPCX™ Office Rich Communication Edition, Release 9.0 and later
- Alcatel-Lucent OmniPCX™ Enterprise Communication Server, starting with Release 11 in manual deployment (please be sure to have analyzed the requested steps for the deployment)
- Alcatel-Lucent OmniPCX™ Enterprise Communication Server, starting with Release 11.0.1, and including Alcatel-Lucent 8770 Network Management option and PMS interworking

* Contact your local sales representative for information on the latest feature list and system compatibility.

** Available on Alcatel-Lucent OpenTouch™ and Alcatel-Lucent OmniPCX™ Office Rich Communication Edition

Standards references (non-exhaustive list)

- RFC 0768 User Datagram Protocol (UDP)
- RFC 0791 Internet Protocol (IP)
- RFC 0793 Transmission Control Protocol (TCP)
- RFC 0826 Address Resolution Protocol (ARP)
- RFC 1321 MD5 Message-Digest Algorithm
- RFC 2131 Dynamic Host Configuration Protocol (DHCP)
- RFC 2617 HTTP Authentication: Basic and Digest Access Authentication
- RFC 2976 SIP INFO Method
- RFC 3261 SIP: Session Initiation Protocol
- RFC 3262 Reliability of Provisional Responses in SIP
- RFC 3263 SIP: Locating SIP Servers
- RFC 3264 An Offer/Answer Model with Session Description Protocol (SDP)
- RFC 3265 SIP-Specific Event Notification
- RFC 3326 The Reason Header Field for the SIP
- RFC 3515 The SIP Refer Method
- RFC 3611 RTP Control Protocol Extended Reports (RTCP XR)
- RFC 3842 A Message Summary and Message Waiting Indication Event Package for the SIP
- RFC 3891 The SIP "Replaces" Header
- RFC 3892 The SIP Referred-By Mechanism
- RFC 3960 Early Media and Ringing Tone Generation in the SIP
- RFC 4566 SDP: Session Description Protocol
- RFC 4733 RTP Payload for DTMF Digits, Telephony Tones, and Telephony Signals
- RFC 5359 Session Initiation Protocol Service Examples
- RFC 1361 Simple Network Time Protocol (SNTP)
- RFC 3748 Extensible Authentication Protocol (EAP)
- RFC 2833 RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals